

## Key Features

Laser Phosphor Technology | Full HD 1080p Resolution | Bright Images  
in any Environment | Horizontal and Vertical Keystone Correction |  
Reduced Input Latency



## Product Description

With incredible Full HD resolution and a high brightness of 3,500 lumens, the ViewSonic® LS700HD laser projector delivers stunning home entertainment: day or night, in bright rooms or dark. Utilizing the latest laser light technology that lasts up to 20,000 hours, the LS700HD delivers long-term enjoyment for movies, games, and other multimedia entertainment. What's more, with high brightness, SuperColor™ technology, and room-filling sound, this projector provides an incredibly immersive home theater experience in nearly any room or environment. Set-up is a breeze too: 1.3x optical zoom and versatile connectivity options allow for more flexible mounting and easy installation. For an amazing home theater viewing experience with lifelike color and razor-sharp details, the LS700HD delivers.




01 Projection Lens  
IR Remote Sensor  
Focus/Zoom Rings  
RS-232  
Computer In  
USB 5V/1.5A Out

02 LAN  
Mini USB  
AC In  
Composite  
Control Panel  
HDMI (x2)




03 Audio In/Out  
04 Monitor Out  
05 Kensington Lock Slot  
06  
07  
08  
09  
10  
11  
12  
13  
14  
15



1920 x 1080  
**RESOLUTION**



3,500 ANSI  
**LUMENS**



1.13~1.47  
**THROW RATIO**

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

Type:	DLP Laser
Resolution Type:	HD (1920x1080)
Resolution:	1920 x 1080
Brightness (Lumens):	3,500 ANSI
Display Size (in.):	60 - 300 in. / 1.5 - 7.6 m
Throw Distance:	4.9 - 28.8 ft / 1.5 - 8.8 m
Throw Ratio:	1.13~1.47
Keystone:	Vertical (± 40°) / Horizontal (± 40°)
Lens:	1.3x Manual optical zoom / manual optical focus
Light Source Life, Normal (hours):	20000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	3,000,000:1
Aspect Ratio:	16:9

**Video Signal:**

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

**Compatibility:**

PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080

**Connector:**

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4 (with HDCP 1.4)(2), VGA In(2), VGA Out(1), Composite RCA Video In(1), Mini USB(1)

**Audio:**

Internal Speakers:	2W (x1)
--------------------	---------

**Power:**

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	260W
Stand-by:	<0.5W

**Controls:**

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

**Operating Conditions:**

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

**Additional Hardware:**

Kensington Lock Slot:	1
-----------------------	---

**Weight (imperial):**

Net (lbs):	15.7
Gross (lbs):	20.1

**Weight (metric):**

Net (kg):	7.1
Gross (kg):	9.1

**Dimensions (imperial) (WxHxD):**

Packaging (in.):	19.7 x 6.2 x 15.8
Physical (in.):	15.6 x 6.2 x 12.4

**Dimensions (metric) (WxHxD):**

Packaging (mm):	500.4 x 157.5 x 401.3
Physical (mm):	396.0 x 157.0 x 314.0

**General:**

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: LS700HD Projector, Power Cable, VGA Cable, Remote Control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

UPC: 766907981216

**Accessories:**

HB10B, IFP2710, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, VC10, VCB10