

Key Features

SuperColor: Amazing Color Accuracy | 4000 Lumen Brightness | Energy Efficient SuperEco | Network Capable | Convenient Mounting Flexibility



Product Description

The ViewSonic® PG707W projector features 4,000 lumens, WXGA 1280 x 800 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. A 10W speaker delivers incredibly clear and audible sound, while a top lamp door enables easy access for lamp maintenance. The PG707W is the ideal high brightness projector for use in both classroom and corporate settings.




- 1. Control Panel
- 2. Elevation Foot
- 3. Zoom Ring
- 4. IR Remote Sensor
- 5. Projection Lens
- 6. VGA In

- 7. HDMI (x2)
- 8. Audio In/Out
- 9. USB 2.0 Type A
- 10. AC In
- 11. Monitor Out
- 12. RCA Video In




- 13. LAN
- 14. Kensington® Lock Slot
- 15. RS232



1280 x 800
RESOLUTION



4,000 ANSI
LUMENS



1.21-1.57
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP Lamp
Resolution Type:	WXGA (1280x800)
Resolution:	1280 x 800
Brightness (Lumens):	4,000 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	2.6 - 33.1 ft / .8 - 10.1 m
Throw Ratio:	1.21-1.57
Keystone:	Vertical (± 40°) / Horizontal (± 40°)
Lens:	1.3x optical zoom
Light Source (watt):	203
Light Source Life, Normal (hours):	6000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Color Depth:	1.07 Billion Colors
Dynamic Contrast Ratio:	22,000:1
Aspect Ratio:	16:10

Video Signal:

Frequency Horizontal:	15K~105KHz
-----------------------	------------

Compatibility:

PC Resolution (max):	1920 x 1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1080
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4 (with HDCP 1.4)(2), VGA In(1), VGA Out(1), Composite RCA Video In(1)

Audio:

Internal Speakers:	10W (x1)
--------------------	----------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	280W
Stand-by:	<0.5W

Controls:

Physical Controls:	Keypad, Power key
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
--------------	-----------------------

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	5.1
Gross (lbs):	7.8

Weight (metric):

Net (kg):	2.3
Gross (kg):	3.5

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.3 x 6.6 x 11.7
Physical (in.):	11.6 x 4.3 x 8.6

Dimensions (metric) (WxHxD):

Packaging (mm):	415.0 x 168.0 x 297.0
Physical (mm):	294.0 x 110.0 x 218.0

General:

Regulations: cTUVus

PACKAGE CONTENTS: PG707W projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907006186

Accessories:

IFP2410, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, PM-FCP, TD2455, VC10, VCB10