



Display:

|                                              |                                           |
|----------------------------------------------|-------------------------------------------|
| Type:                                        | DLP Lamp                                  |
| Resolution:                                  | 3840 x 2160                               |
| Display Size (in.):                          | 30 - 300 in. / 0.76 - 7.62 m              |
| Throw Distance:                              | 0.75m~9.76m (100"@2.50m)                  |
| Throw Ratio:                                 | 1.13-1.47                                 |
| Keystone:                                    | Vertical (+/- 40º) / Horizontal (+/- 40º) |
| Lens:                                        | 1.3x optical zoom                         |
| Light Source (watt):                         | 240                                       |
| Light Source Life, Normal (hours):           | 4000                                      |
| Light Source Life, Dynamic Eco-Mode (hours): | 20000                                     |
| Color Depth:                                 | 1.07B Color (R/G/B 10bit)                 |
| Dynamic Contrast Ratio:                      | 12,000:1                                  |
| Aspect Ratio:                                | 16:9                                      |

Video Signal:

|                       |            |
|-----------------------|------------|
| Frequency Horizontal: | 15K-129KHz |
| Frequency Vertical:   | 23-240Hz   |

Compatibility:

|                        |             |
|------------------------|-------------|
| PC Resolution (max):   | 3840 x 2160 |
| Mac® Resolution (max): | 3840 x 2160 |

Connector:

USB 2.0 Type A(1), USB 3.1 Type C(1), Ethernet LAN (RJ45)(1), 3.5mm 12V Trigger(1), 3.5mm Audio Out(1), Control (RS232)(1), HDMI 2.0 (with HDCP 2.2)(2)

Audio:

|                    |          |
|--------------------|----------|
| Internal Speakers: | 10W (x1) |
|--------------------|----------|

Power:

|                        |                             |
|------------------------|-----------------------------|
| Voltage:               | 100-240V+/- 10%, 50/60Hz AC |
| Consumption (typical): | 310W                        |
| Stand-by:              | <0.5W                       |

Controls:

|                    |                                                                                                                    |
|--------------------|--------------------------------------------------------------------------------------------------------------------|
| Physical Controls: | Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source                  |
| On Screen Display: | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |

Operating Conditions:

|                            |                       |
|----------------------------|-----------------------|
| Temperature:               | 32-104º F (0 - 40º C) |
| Humidity (non-condensing): | 0-90%                 |

Additional Hardware:

|                       |   |
|-----------------------|---|
| Kensington Lock Slot: | 1 |
|-----------------------|---|

Weight (imperial):

|              |     |
|--------------|-----|
| Net (lbs):   | 6.2 |
| Gross (lbs): | 8.8 |

Weight (metric):

|             |     |
|-------------|-----|
| Net (kg):   | 2.8 |
| Gross (kg): | 4.0 |

Dimensions (imperial) (WxHxD):

|                  |                   |
|------------------|-------------------|
| Packaging (in.): | 16.3 x 6.6 x 11.7 |
| Physical (in.):  | 12.2 x 8.7 x 4.3  |

Dimensions (metric) (WxHxD):

|                 |                       |
|-----------------|-----------------------|
| Packaging (mm): | 415.0 x 168.0 x 297.0 |
| Physical (mm):  | 312.0 x 222.0 x 108.0 |

General:

|                   |                                                                        |
|-------------------|------------------------------------------------------------------------|
| Regulations:      | FCC, cTUVus, ROHS                                                      |
| PACKAGE CONTENTS: | Projector, power cable, remote control, USB-C Cable, Quick Start Guide |
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws.     |
| UPC:              | 766907008951                                                           |

Accessories:

|                                                             |
|-------------------------------------------------------------|
| HB10B, PJ-CASE-008, PJ-SCW-1001W, PJ-WMK-006, VCB10, VSR100 |
|-------------------------------------------------------------|